RECEIVED
CENTRAL FAX CENTER

11/19/2009 12:20 7036217155

NOV 1 9 2009

PAGE 03/09

Serial No. 10/594,950

Reply to Office Action dated August 19, 2009

Docket No. 2003/0101PUS1

**Amendments to the Claims:** 

This listing of claims will replace all prior versions, and listings, of claims in the

MGIP

application:

**Listing of Claims:** 

Please amend the claims as follows:

1. (Currently Amended)A fitting for a child safety seat for use with a vehicle seat

comprising:

a body;

provided to said body, a first connector for connecting to an anchorage of a child

safety seat; and

provided to the body and spaced from the first connector, a second connector for

connecting to an anchorage of a vehicle seat wherein the body has elongate form and

the first and second connectors are provided at opposing ends thereof, and wherein

both the first and second connectors conform to the ISOfix standard.

2. (Cancelled)

3. (Previously Presented) A fitting according to claim 1, comprising a first body part, a

second body part and a crosspiece therebetween to define an overall H-form body; and

provided to each body part, a first connector for connecting to an anchorage of a child

safety seat; and spaced from the first connector, a second connector for connecting to

an anchorage of a vehicle seat.

2

Serial No. 10/594,950 Reply to Office Action dated <u>August 19, 2009</u>

Docket No. <u>2003/0101PUS1</u>

- 4. (Original) A fitting according to claim 3, wherein the crosspiece has box girder form.
- 5. (Previously Presented) A fitting according to claim 1, wherein the body is provided with guide elements for guiding the first and second connectors to connect with their respective anchorages.
- 6. (Cancelled)
- 7. (Cancelled)
- 8. (Previously Presented) A fitting according to claim 1, wherein the body comprises an adjuster for adjusting the spacing between the first and second connectors.
- 9. (Original) A fitting according to claim 8, wherein said adjuster allows for continuous adjustment of the spacing over a defined range of spacing distances.
- 10. (Original) A fitting according to claim 9, wherein the spacing adjuster comprises a screw adjuster.
- 11. (Original) A fitting according to claim 8, wherein the adjuster allows for stepped adjustment of the spacing over a defined range of spacing distances.
- 12. (Original) A fitting according to claim 11, wherein the spacing adjuster comprises a

Serial No. 10/594,950 Reply to Office Action dated <u>August 19, 2009</u>

Docket No. 2003/0101PUS1

ratchet and pawl mechanism.

13. (Original) A fitting according to claim 11, wherein the spacing adjuster comprises a sprung-loaded spacer pin that is movable between defined spacing positions.

14. (Previously Presented) A fitting according to claim 1, wherein one or more of the first and second connectors locates within a recess defined by an open jaw.

15. (Previously Presented) A fitting according to claim 1, wherein one or more of the first and second connectors is arranged such as to automatically lock onto the anchorages on being brought into contact therewith.

16. (Previously Presented) A fitting according to claim 1, additionally comprising one or more releases for ready release of one or more of the first or second connectors.

17. (Original) A fitting according to claim 16, wherein each release comprises a user actuator that couples via a release mechanism to a connector.

18. (Currently Amended) A fitting according to claim 48 17, wherein the release mechanism comprises a latch mechanism.

19. - 29. (Cancelled)